

Solar Flood Light

High performance LED luminaire with efficient solar and Lithium battery technology. Ideal replacement for traditional lighting sources or applications. Solar Lighting naturally doubles as an exterior emergency light in the case of a power outage. Suitable for assembly point illumination.



Applications Remote Signs, Walkways, Carparks
Colours Black

\$0 Power - \$0 Trenching Cost - \$0 Cabling

Technical Summary

Light Source	Bridgelux	Body	Die-Cast Aluminium AKZONOBEL coating
Battery Voltage	15-24Ah Lithium LIFEP04	Optic	PC High Diffusion UV Resistant Optic
Colour Temperature	5000K	Life Expectancy L70	40,000 hrs
Efficacy	120-125 Lm/W	IP Rating	IP67
Solar Panel	50-80W Monocrystal Panel	Warranty	5 Years

Product Information

Product Code	Solar Panel	Luminaire Power	Lumens	Dimensions Fixture	Dimensions PV	Weight
EST-SLK-015	50W	15W	1800	380x255x100mm	710x510x138mm	9.25Kg
EST-SLK-020	60W	20W	2500	270x200x50mm	700x510x138mm	17.0Kg
EST-SLK-030	80W	30W	3600	270x200x50mm	740x670x138mm	18.0Kg