

Product data sheet

Characteristics

CLITPDL1C1

Clipsal - LED downlight, 9W, >700 lm, 3000K/4000K/6000K, IP44, white trim

Main

Range	Clipsal
Product name	TPDL1C1 Series
Product or component type	Downlight
Device application	Lighting
Market segment	Residential Small commercial

Complementary

Device mounting	Recessed ceiling
Shape	Round
Type of installation	Indoor
Rated power in W	9 W
Light source	LED
Total system power	240 V AC 50 Hz
Luminous flux	700 lm 3000 K warm white 730 lm 4000 K cool white 750 lm 6000 K day light
Colour rendering index	R _a =80
Bulb lifespan	30000 h
Beam angle	90 °
Function available	Integrated switch for temperature colour selection Energy efficiency
Load type	Dimmable LED
Range compatibility	dimmer
Device composition	Plastic integral dimming driver Round white metal twist exchangeable trim Lens recessed Flex plug
Quantity per set	1
Trim width	110 mm
Cut-out dimensions	90 mm
Mounting depth	65 mm
Net weight	0.227 kg

Environment


IP degree of protection	IP44
Insulation contact rating	IC-4
Ambient air temperature for operation	-10...45 °C
Relative humidity	10...95 % non-condensing

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Package 1 Weight	0.252 kg
Package 1 Height	120.000 mm
Package 1 width	120.000 mm
Package 1 Length	120.000 mm

Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	 China RoHS Declaration