

LED LOW PROFILE BATTEN



PRODUCT DETAILS:




- Size: 4ft/1200mm, 5ft/1500mm
- Rated life: L70/B10 50000hrs
- LED: CCT 4000K/6000K, CRI>80
- Driver: Integral, Non-Dim
- Operating temperature: 0°C to +40°C
- Housing: Cold rolled steel
- Finishing: White
- Diffuser: Polycarbonate, Frosted, Reeded
- Connection: 20mm knockout for conduit or cable glands from end or rear, Center cable entry, End to end mounting
- Warranty: 5 year

MADE TO ORDER OPTIONS:

DALI/PUSH/1-10V dimming, Emergency

APPLICATIONS:

Surface mount, Internal
Commercial, Retail, Residential



5FT/1500MM 4000K 57W

VERSION	L (MM)	W (MM)	H (MM)
4FT/1200MM	1192	81	50
5FT/1500MM	1498	81	50

CODE	DESCRIPTION	POWER [~]	LUMENS ⁺	EFFICACY
LEDBAT/4/4K	4FT/1200MM 40W 4000K CRI>80 NON-DIM	38W	3433lm	90lm/W
LEDBAT/4/6K	4FT/1200MM 40W 6000K CRI>80 NON-DIM	39W	3516lm	90lm/W
LEDBAT/5/4K	5FT/1500MM 58W 4000K CRI>80 NON-DIM	57W	5579lm	98lm/W
LEDBAT/5/6K	5FT/1500MM 58W 6000K CRI>80 NON-DIM	57W	5579lm	98lm/W

*Delivered lumens from luminaire, including thermal, electrical and optic losses. [~]Tested system powers from luminaire.