

Recessed Retrofit Dimmable Downlight IP44 Smart Tilt

R692

goLink



RETROFIT
Fits 82mm Cut
Outs



SPECIFICATIONS

DIMENSIONS	D96 x H79mm
CUT OUT	Ø 82-84mm
CCT / LUMENS	3000K Warm White 830lm 4000K Natural White 870lm 3000-2000K Sunset Dim 550lm
IP RATING	IP44
CRI	Standard / CRI90 Sunset Dim / CRI95
LIFESPAN	50,000 Hours (L70)
WARRANTY	5 Year Warranty
BEAM ANGLE	60°
TILT ANGLE	30° (Patented IP44 tilt gasket)
MATERIAL	Aluminum and Patented PC Heat Shield
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC Rated
DRIVER	Under Insulation Dimmable Go Link 260mA Driver features power indicator safety light
APPLICATION	Interior only, suitable for new and retrofit applications

<870 LUMENS	9.5 WATTS	AC 240V
---------------------------	----------------------	--------------------

	UID™ Dimmable Under Insulation Go Link Driver Included
---	--

AVAILABLE IN

DESCRIPTION	CODE
White 3000K	R692 W3K
White 3000K 10 Pack (CRI80, 900lm)	R692 W3K10
White 4000K	R692 W4K
White 3K-2K Sunset Dim	R692 W32K
Black 3000K	R692 B3K
Black 4000K	R692 B4K
Silver 3000K	R692 S3K
Brushed Chrome 3000K	R692 BC3K