

## Drivers Constant Voltage PSTW Series 24V



SPECIFICATION									
<b>CODE</b>	PSTW-24V-12W	PSTW-24V-20W	PSTW-24V-40W	PSTW-24V-50W	PSTW-24V-60W	PSTW-24V-75W	PSTW-24V-100W	PSTW-24V-150W	
<b>WATTS OUTPUT</b>	1-12Watt	1-20Watt	1-40Watt	1-50Watt	1-60Watt	1-75Watt	1-100Watt	1-150Watt	
<b>VOLTS OUTPUT</b>	24Volts DC								
<b>AMPS OUTPUT</b>	0.5Amps	0.83Amps	1.7Amps	2.1Amps	2.5Amps	3.1Amps	4.16Amps	6.25Amps	
<b>VOLTS INPUT</b>	220-240VAC 50~60Hz								
<b>POWER FACTOR</b>	0.80	0.80	0.95	0.95	0.95	0.95	0.95	0.95	
<b>IP RATING</b>	IP20								
<b>DIMENSIONS</b>	98 x 39 x 22	113 x 44 x 28	166 x 52 x 24	184 x 61 x 32	184 x 61 x 32	184 x 61 x 32	184 x 61 x 32	210 x 67 x 34	
<b>PROTECTION</b>	Safe no load, Short circuit, Over temp, Class II, SELV.								
<b>WORKING TEMP</b>	-20 to +50degC						-20 to +45degC		-20 to +45degC.
<b>EMC</b>	EMC compliant.								
<b>SAFETY</b>	Tested to AS/NZS requirements.								
<b>WARRANTY</b>	3 Years								

### FEATURES:

- # Large terminals for looping TPS.
- # Covered 230V terminals.
- # SELV & Class 2
- # Warranty 3 years.

### NOTE:

- \*\* Note IP20 for indoor use only or exterior when housed in a suitable enclosure for exterior use.
- \*\* Do not cover with insulation and allow for good ventilation.

### APPLICATIONS:

- # Power 24VDC LED strips & lamps.
- # Suitable for supplying power to 24VDC dimmed loads like PWM (pulse width modulation) dimmed loads & 24VDC RGB colour changing loads.

While every effort has been made to ensure the accuracy of all information provided Task Lighting can not be held responsible for any errors. Task Lighting also reserves the right to modify/delete product details without notice.