



Main

Range of product	56 Series™
Product or component type	Rotary switch
Colour tint	White
Motor M-rating AS3133	M180
Quantity per set	Set of 4
Type of packing	Carton

Complementary

Number of poles	3
Control type	Rotary
Material	PBT (polybutylene terephthalate)
Surface finish	Gloss
Installation direction	Vertical
Width	95 mm
Height	95 mm
Depth	48 mm
Rated current	32 A
[Ue] rated operational voltage	415 V
[Ui] rated insulation voltage	660 V
Network frequency	50 Hz
Network number of phases	3 phases
Number of gangs	1 gang
Mounting mode	Surface mounted
Fixing center	84 x 84 mm
Cable cross section	1...16 mm ²

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Environment

IP degree of protection	IP66
Ambient air temperature for operation	-40...55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.239 kg
Package 1 Height	60 mm
Package 1 width	95 mm
Package 1 Length	95 mm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile