Product data sheet Characteristics

PDL56SW4202KGLERO

Switch - KG Series, 20A, 500V, 4-Pole, 2-Gang, Resistant Orange



Main

Range of product 56 Series™ Product or component type Rotary switch Colour tint Orange Quantity per set Set of 4 Type of packing Carton	Mairi		
Colour tint Orange Quantity per set Set of 4	Range of product	56 Series™	- -
Quantity per set Set of 4	Product or component type	Rotary switch	
	Colour tint	Orange	
Type of packing Carton	Quantity per set	Set of 4	
	Type of packing	Carton	

Complementary

Number of poles	4	
Control type	Rotary	
Material	PBT (polybutylene terephthalate)	±
Surface finish	Gloss	
Installation direction	Vertical	
Width	95 mm	
Height	190 mm	-
Depth	66 mm	
Rated current	20 A	-
[Ue] rated operational voltage	500 V	
[Ui] rated insulation voltage	690 V	+
Network frequency	50 Hz	. <u>.</u> .
Network number of phases	3 phases	
Number of gangs	2 gangs	
Mounting mode	Surface mounted	
Fixing center	180 X 84 mm	0 0
Cable cross section	16 mm²	

Environment

IP degree of protection	IP66
Ambient air temperature for operation	-4055 °C

195.500 g