

PRODUCT CODE: MSEC 6072TCW

6 Core 0.22mm (7/0.2) Tinned Copper, ACA3166 Security Cable

EXTRA LOW VOLTAGE – NOT FOR MAINS CONNECTION



CONSTRUCTION	
PRODUCT CODE	100m = MSEC 6072/100 TCW 300m = MSEC 6072/300 TCW
CONDUCTOR	Stranded, Tinned, Oxygen Free Plain Copper Wire to AS1125 $\phi = 7 \times 0.20 \pm 0.005 \text{ mm} \times 6$ Max. conductor DC resistance @ 20°C: 89.5 ohms/Km Amp Rating: 1.4
INSULATION	PVC RoHS Flame Retardant (AS/NZS 3808) $\phi = 1.25 \pm 0.05 \text{ mm} \times 6$ Colour: Red, Blue, White, Black, Green, Yellow Thickness: 0.3mm \pm 0.05mm Voltage Rating: 300V
OUTER JACKET	PVC RoHS Compliant 75°C PVC to AS3808, Flame Retardant Colour: White Thickness: 0.60mm \pm 0.05mm
NOMINAL O.D (mm)	$\phi = 5.4 \pm 0.10 \text{ mm}$
PACKAGE	100m Plastic Reel (5 Reels per box) 300m Reel in a Box
CABLE MARKING	MASER SECURITY SOLUTIONS MSEC6072 0.22mm ² TCW ACA3166 SECURITY CABLE EXTRA LOW VOLTAGE DD/MM/YYYY 001M-100M-300M

TDS# MSEC6072TCW 06042016v1

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.