

# FLEXIBLE DUCTING - ComFlex Premium

Diameter (mm)	Length (m)	Thermally Insulated	
		Nude	R0.6 (40mm)
		Order Code	Order Code



100	3	DCT0215	DCT0452
	6	DCT0104	
125	3	DCT0216	
	6	DCT0160	
150	3	DCT0217	DCT0427
	6	DCT0107	DCT0428
200	3	DCT0218	DCT0429
	6	DCT0109	DCT0430
250	3	DCT0219	DCT0431
	6	DCT0421	DCT0432
300	3	DCT0111	DCT0433
	6	DCT0422	DCT0434
350	3	DCT0112	DCT0435
	6	DCT0423	DCT0436
400	3	DCT0113	DCT0437
	6	DCT0424	DCT0438

- Complies to AS1530 PT3 and New Zealand Building Code
- DUCT CORE: Polyester film core with aluminium foil laminated onto both sides
- This composite film is then permanently bonded onto a corrosion resistant coated, spring steel wire helix
- DUCT SLEEVE: Fire retardant 75µm black low density UV-stabilised polyethylene
- DUCT INSULATION: Polyester R0.6 nominal
- TEMPERATURE RANGE: Nude Core - Maximum: +150°C, Minimum: -30°C
- COLOUR: Silver with black sleeve

## Note

1. No glued/adhesive duct should be installed in a compressed or ovalised state for fear of long term failure.