



### Main

Range compatibility	PDL Iconic cover plate Pro Series cover plate
Product brand	PDL
Range	Iconic
Product or component type	Dimmer

### Complementary

Device presentation	Mechanism
Dimmer type	Universal
Load type	Dimmable LED: 0...150 W Compact fluorescent lamp: 0...300 W Incandescent lamp: 0...300 W at 240 V Halogen lamp: 0...300 W at 240 V LV halogen lamps: 0...300 W (electronic transformer)
[Ue] rated operational voltage	220...240 V AC 50 Hz
Protection type	Overheating protection Short-circuit protection Overcurrent protection
Colour tint	Vivid white (VW)
Local signalling	LED
Control type	Push-button By mobile application Multi-way control via ControlLink
Number of ways	5 ways
Software name	Wiser by SE App Wiser App: random function Wiser App: enable wake-up function Wiser App: enable fall-asleep function Wiser App: management of the staircase timer (with/without warning) Wiser App: light control
Maximum number of connected devices	3 (dimmer) 2 (ControlLink module)
Cable length	50 m for ControlLink module
Technology type	Bluetooth low energy default Zigbee

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Memory description	Backup memory - date and time for 6 h Backup memory - program for indefinite period
Wiring configuration	3-wire
Material	Plastic
Mounting support	Grid
Device mounting	Flush
Fixing mode	Clip-in
Fixing center	84 mm
Type of installation	Indoor installation
Embedding depth	70 mm
Depth	56 mm
Width	48 mm
Height	22 mm

## Environment

IP degree of protection	IP20
Relative humidity	5...90 % non-condensing
Standards	AS/NZS 60669.2.1 safety AS/NZS 60669.2.1 EMC AS/NZS 4268 radio

## Packing Units

Package 1 Weight	30.000 g
Package 1 Height	39.000 mm
Package 1 width	67.000 mm
Package 1 Length	87.000 mm