Clight DOWNLIGHT







FEATURES

- PBT+AL1060+PC body
- Opal acrylic diffuser
- Built-in trailing edge dimmable LED driver
- Select colour temperature with DIP switch
- LED lifespan: 50000 Hours @L70, Ta 25°C
- Ta: -20°C°C to +40°C

DIMENSION

Select colour temperature with DIP switch

OPTIONS

Н

- Metal Frame Cover: Black / Satin Nickel -GDL 804 SN Ring
- -GDL 804 BK Ring -GDL 805 SN Ring -GDL 805 BK Ring



rofit jobs, for some of the houses they have 125mm cut out size downlight, but don't

want overly bright.

TECHNICAL SPECIFICATIONS

Ø

MODEL NO.	INPUT VOLTAGE (V)	POWER (W)	LUMEN (lm)	COLOUR TEMPERATURE (K)	BEAM ANGLE (°)	DIMENSIONS (Ø×H)	CUT OUT SIZE (Ø) (mm)	FITTING COLOUR	CARTON QUANTITY
GDL804 TC WH	230	7	550/624/600	3000/4000/5700	90	90 X 56	70	White	64
GDL805 TC WH	230	9	800/880/850	3000/4000/5700	90	110 X 65	90	White	40
GDL807 TC WH	230	9	800/880/850	3000/4000/5700	90	145 X 65	125	White	40
GDL809 TC WH	230	14	1132/1282/1168	3000/4000/5700	90	145 X 65	125	White	40

Operation of the second sec