

## Product data sheet

### Characteristics

# PDL89DI

## Universal Double Insulated Mounting Block; Polycarbonate, White



### Main

Range of product	PDL General Accessories
Product or component type	Mounting plate
Colour tint	White
Quantity per set	Set of 8
Type of packing	Carton

### Complementary

Material	PC (polycarbonate)
Surface finish	Glossy
Installation direction	Horizontal Vertical
Device mounting	Surface
Width	74 mm
Depth	44 mm
Length	118 mm
Fixing center	84 mm



### Environment

Ambient air temperature for operation	-10...40 °C
---------------------------------------	-------------

### Packing Units

Package 1 Weight	116.000 g
------------------	-----------

### Offer Sustainability

EU RoHS Directive	Under investigation
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.