

■ QUICK ASSEMBLY STRAIGHT PLUGS **SERIES 690**

MAIN TECHNICAL FEATURES:

- Straight industrial plugs according to the Standard EN 60309.
- In currents of 16 and 32 A.
- Protection degree IP44.
- Fast assembly without tools, screw terminals.
- Resistance to chemical or atmospheric agents.

CE

IP44

■ Quick assembly straight plugs - EN 60309 - In 16A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC69470	■	2P	20-25 V~	without reference	10/80
EC69471	■	3P	20-25 V~	without reference	10/80
EC69170	■	2P+⊕	100-130 V~	4	10/80
EC69171	■	3P+⊕	100-130 V~	4	10/80
EC69070	■	2P+⊕	200-250 V~	6	10/80
EC69270	■	3P+⊕	200-250 V~	9	10/80
EC69271	■	3P+N+⊕	208-250 V~	9	10/80
EC69072	■	3P+⊕	380-415 V~	6	10/80
EC69074	■	3P+N+⊕	346-415 V~	6	10/80

■ Quick assembly straight plugs - EN 60309 - In 32A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC69172	■	2P+⊕	100-130 V~	4	10/80
EC69173	■	3P+⊕	100-130 V~	4	10/80
EC69272	■	2P+⊕	200-250 V~	6	10/80
EC69273	■	3P+⊕	200-250 V~	9	10/80
EC69076	■	3P+⊕	380-415 V~	6	10/80
EC69078	■	3P+N+⊕	346-415 V~	6	10/60



EC69170



EC69070



EC69072