

## ■ QUICK ASSEMBLY STRAIGHT SOCKETS **SERIES 690**

### MAIN TECHNICAL FEATURES:

- Straight industrial plugs according to the Standard EN 60309.
- In currents of 16 and 32 A.
- Protection degree IP44.
- Stainless steel springs for lid closing.
- Fast assembly without tools.
- Screw terminals.
- Resistance to chemical or atmospheric agents.

CE

IP44

## ■ Quick assembly straight sockets - EN 60309 - In 16A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC69480	■	2P	20-25 V~	without reference	10/80
EC69481	■	3P	20-25 V~	without reference	10/80
EC69180	■	2P+⊕	100-130 V~	4	10/80
EC69181	■	3P+⊕	100-130 V~	4	10/80
EC69080	■	2P+⊕	200-250 V~	6	10/80
EC69280	■	3P+⊕	200-250 V~	9	10/80
EC69281	■	3P+N+⊕	208-250 V~	9	10/80
EC69082	■	3P+⊕	380-415 V~	6	10/80
EC69084	■	3P+N+⊕	346-415 V~	6	10/80

## ■ Quick assembly straight sockets - EN 60309 - In 32A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC69182	■	2P+⊕	100-130 V~	4	10/60
EC69183	■	3P+⊕	100-130 V~	4	10/60
EC69282	■	2P+⊕	200-250 V~	6	10/60
EC69283	■	3P+⊕	200-250 V~	9	10/60
EC69086	■	3P+⊕	380-415 V~	6	10/60
EC69088	■	3P+N+⊕	346-415 V~	6	10/40



EC69180



EC69080



EC69082