

## ■ WALL MOUNTING INCLINED BOX PLUGS **SERIES 690**

### MAIN TECHNICAL FEATURES:■

- 15° Inclined industrial plugs according to the Standard EN 60309.
- Wall mounting inclined box, with M25 threaded inlet with closure cap included.
- In currents of 16 and 32 A.
- Resistance to chemical or atmospheric agents.
- Shock resistance: IK08 (up to 6J).
- 16A Dimensions: 120x71x80 mm, centre hole 58 mm.
- 32A Dimensions: 132x71x85 mm, centre hole 58 mm.

CE

IP44

## ■ Wall mounting inclined box plugs - EN 60309 - In 16A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC690701		2P+⊕	200-250 V~	6	10/40
EC690721		3P+⊕	380-415 V~	6	10/40
EC690741		3P+N+⊕	346-415 V~	6	10/40

## ■ Wall mounting inclined box plugs - EN 60309 - In 32A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC692721		2P+⊕	200-250 V~	6	10/40
EC690761		3P+⊕	380-415 V~	6	10/40
EC690781		3P+N+⊕	346-415 V~	6	10/40



EC690701



EC690721



EC690781