

Cable Breakout

Application

Insulation and sealing over the crutch of multi-core cables. The hot melt adhesive provides a water tight environmental seal to the cable. The LV breakouts are used as an integral part of cable terminations up to 1kV. Heat shrinkable low voltage breakouts whose dimension will shrink to a pre-determined size upon the application of heat above 125°C.

Typical feature

- > Color : black
- > Finger No. : 2-4.
- > Hot melt : poly-amide based hot melt adhesive.

2 CORE Breakout Boots

Order Code	Description	Pack	Qty
LS CB 23310 / IXL 250	2-Core Low Voltage (LV) Breakout Boot 4-35mm	Each	1
LS CB 26022 / IXL 260	2-Core Low Voltage (LV) Breakout Boot 35-150mm	Each	1



3 CORE Breakout Boots

Order Code	Description	Pack	Qty
LS CB 32808 / IXL300	3-Core Low Voltage (LV) Breakout Boot 1-10mm	Each	1
LS CB 33814 / IXL 350	3-Core Low Voltage (LV) Breakout Boot 4-35mm	Each	1
LS CB 36022 / IXL 360	3-Core Low Voltage (LV) Breakout Boot 50-150mm	Each	1
LS CB 38033 / IXL 370	3-Core Low Voltage (LV) Breakout Boot 185-300mm	Each	1
LS CB 311047 / IXL 380	3-Core Low Voltage (LV) Breakout Boot 300-400mm	Each	1
LS CB 312547 / IXL 390	3-Core Low Voltage (LV) Breakout Boot 400-630mm	Each	1



4 CORE Breakout Boots

Order Code	Description	Pack	Qty
LS CB 42808 / IXL400	4-Core Low Voltage (LV) Breakout Boot 1-10mm	Each	1
LS CB 43814 / IXL 415	4-Core Low Voltage (LV) Breakout Boot 4-35mm	Each	1
LS CB 46525 / IXL 420	4-Core Low Voltage (LV) Breakout Boot 35-70mm	Each	1
LS CB 47222 / IXL 430	4-Core Low Voltage (LV) Breakout Boot 70-150mm	Each	1
LS CB 410033 / IXL 440	4-Core Low Voltage (LV) Breakout Boot 185-300mm	Each	1
LS CB 412547 / IXL 450	4-Core Low Voltage (LV) Breakout Boot 300-500mm	Each	1



5 CORE Breakout Boots

Order Code	Description	Pack	Qty
LS CB IXL527	5-Core Low Voltage (LV) Breakout Boot 2.5-95mm	Each	1
LS CB IXL545	5-Core Low Voltage (LV) Breakout Boot 95-300mm	Each	1

